Veedol

INDUSTRIAL OILS

HYDRAULIC AND CIRCULATION OILS

- VEEDOL AVALON 32 • VEEDOL AVALON 46
- VEEDOL AVALON 68 • VEEDOL AVALON 100
- VEEDOL AVALON 150 • VEEDOL AVALON 220
- VEEDOL AVALON 320 • VEEDOL AVALON 460

DESCRIPTION

- Solvent refined high viscosity index mineral oils fortified with anti-wear, anti-oxidation, anti-corrosion and anti-foam additives.
- Available ISO Viscosity Grades – 32, 46, 68, 100, 150, 220, 320 & 460.
- Conform to IS 10522 : 83 specifications (reaffirmed in 1993).

APPLICATIONS

- Recommended for circulation systems and other enclosed systems like bearings and gears of general machinery.

BENEFITS

- Excellent resistance to oxidation.
- Outstanding anti-wear protection.
- Excellent rust & corrosion protection.

CHARACTERISTICS

VEEDOL AVALON		32	46	68	100	150	220	320	460
Kin. Vis. cSt at 40°C	Min	28.8	41.4	61.2	90	135	198	288	414
	Max	35.2	50.6	74.8	110	165	242	352	506
Viscosity Index	Min	95	95	95	95	95	95	95	95
Flash Point (COC) °C	Min	200	210	210	220	220	230	230	230
Pour Point °C	Max	-6	-6	-6	-6	-6	-6	-6	-6
Copper Strip Corrosion	Max	Not Worse Than 1							
Rust Test		Pass	Pass	Pass	Pass	Pass	Pass	Pass	Pass