



PRODUCT DATA SHEET

HDC TURBO SPRINT 15W-40 API CF-4 (DIESEL ENGINE OIL)

Description

Viscometrics – SAE 15W-40
Exceeds API CH-4 performance standard

Application

HDC TURBO SPRINT 15W-40 API CF-4 are viscometrics – SAE 15W-40. Meets the requirements of API CF-4, ACEA A2/B2, MB 228.0/ 228.1, MAN 270/ 271, Volvo VDS, Mack EO/K-2

Product Benefits

High Viscosity Index helps in easy cold starting and retains adequate film thickness over a wide temperature range

Characteristics

		15W-40 API CF-4
Kin. Vis. cSt at 100°C	Min	14
	Max	16.5
Viscosity Index	Min	135
Flash Point (COC) °C	Min	220
Pour Point °C	Max	-24

TIDE WATER OIL CO. (INDIA) LTD.

Registered Office: Yule House | 8, Dr. Rajendra Prasad Sarani | Kolkata 700 001
Tel: 033 2242 1086 | Fax: 033 2242 1087 | E-mail: tidecal@tidewaterindia.co.in

Northern Region: 1201-1207, 'A' Block | 12th Floor | Naurang House | 21, Kasturba Gandhi Marg | New Delhi 110 001
Tel: 011 2375 2803-06 | Fax: 011 2335 9254 | Email: mailnr@tidewaterindia.co.in

Western Region: CTS 90 | Kachwadi | Deonar | Govandi (East) | Mumbai 400 088
Tel: 022 6138 6444/99 | Fax: 022 6138 6477/88 | Email: mailwr@tidewaterindia.co.in

Southern Region: Seshachalam Centre | 10th Floor | 636/1, Anna Salai | Nandanam | Chennai 600 035
Tel: 044 3096 9000/2434 9050 | Fax: 044 3096 9050/2434 7994 | Email: rosouth@tidewaterindia.co.in

Website: www.tidewaterindia.com