

## INDUSTRIAL OILS

### TURBINE OILS

- VEEDOL ATURBRIO 32 • VEEDOL ATURBRIO 46
- VEEDOL ATURBRIO 68

### DESCRIPTION

- Available ISO Viscosity Grades – 32, 46 & 68.
- Made from the finest base-stocks and are specially refined to ensure maximum resistance to sludging and emulsification.
- Conforms to IS 1012 : 1987 specification.

### APPLICATIONS

- Recommended for steam and water turbines, hydraulic systems, cylinders and bearings of multistage compressors, torque convertors etc., where long life lubricants of outstanding properties are required.

### BENEFITS

- Possess excellent chemical and oxidation stability.
- Blended with rust and oxidation inhibitors and anti-foam agents for a long service life.

### CHARACTERISTICS

VEEDOL ATURBRIO		32	46	68
Kin. Vis. cSt at 40°C	Min	28.8	41.4	61.2
	Max	35.2	50.6	74.8
Viscosity Index	Min	100	100	100
Flash Point (COC) °C	Min	200	200	200
Pour Point °C	Max	-6	-6	-6
Copper Strip Corrosion	Max	1	1	1
Rust Test		Pass	Pass	Pass
Emulsion Characteristic				
at 54 °C, ml (40-40-0), Mins	Max	20	25	25
Air Release Value, Mins	Max	5	7	11