

## INDUSTRIAL OILS

### HEAVY DUTY HYDRAULIC OILS

- VEEDOL AVALON HLP 32 • VEEDOL AVALON HLP 46
- VEEDOL AVALON HLP 68 • VEEDOL AVALON HLP 100
- VEEDOL AVALON HLP SC – 6 32
- VEEDOL AVALON HLP SC – 6 46
- VEEDOL AVALON HLP SC – 6 68

### DESCRIPTION

- Premium grade anti-wear extreme pressure high viscosity index hydraulic oils with excellent anti-wear, oxidation stability and rust preventive properties.
- Avalon HLP SC-6 oils belong to the category of super clean hydraulic oil and passes the cleanliness requirements of Class 6 of NAS 1638 standards.
- Conforms to IS 11656 : 86 and DIN 51524 Part 2 specification.

### APPLICATIONS

- Recommended for high pressure hydraulic systems and also for systems where high pump speeds are encountered.

### BENEFITS

- Maintains good lubrication over a wide temperature range.

### CHARACTERISTICS

VEEDOL AVALON HLP		32	46	68	100
Kin. Vis. cSt at 40°C	Min	28.8	41.4	61.2	90
	Max	35.2	50.6	74.8	110
Viscosity Index	Min	95	95	95	95
Flash Point (COC) °C	Min	200	210	220	220
Pour Point °C	Max	-18	-15	-12	-12
Rust Test		Pass	Pass	Pass	Pass
Oxidation Stability Test		Pass	Pass	Pass	Pass
Wear Test		Pass	Pass	Pass	Pass