



## Heavy Pull Pro 20W-50 SN

High Performance Multigrade Engine oil  
Synthetic Blend

### PRODUCT DATA SHEET

#### Product Description:

Veedol Heavy Pull Pro 20W-50 SN is a high-quality synthetic blend engine oil specifically designed for small commercial vehicles powered by CNG, LPG or Petrol. It provides superior protection and performance even under the demanding driving conditions.

Veedol Heavy Pull Pro 20W-50 SN offers high thermal stability, oxidation protection, and wear resistance keeping the engine running smoothly and efficiently.

#### Performance Specification:

Veedol Heavy Pull Pro 20W-50 SN meets and exceeds below performance

API SN

#### Features/Benefits:

- **Superior protection:** High performance anti-wear additive in the formulation provides superior protection to engine components reducing maintenance costs.
- **Excellent heat resistance:** The synthetic blend oil offers excellent heat resistance, preventing oil breakdown and ensuring reliable engine performance even under high-temperature conditions.
- **Dual-fuel performance:** Provides very good performance for medium and light-duty vehicles fueled with CNG, LPG as well as conventional fuels.

#### Application:

- Recommended for small commercial vehicles running on CNG, LPG or conventional fuels.

#### Typical Properties:

Parameters	Test Method	Results
Density @ 29.5°C	ASTM D4052	0.873
Kinematic Viscosity @ 40°C, cSt	ASTM D445	160.1
Kinematic Viscosity @ 100°C, cSt	ASTM D445	18.75
Viscosity Index	ASTM D2270	132
Flash Point (COC), °C	ASTM D92	252
Pour Point, °C	ASTM D97	-30
Total Base Number, mg KOH/g	ASTM D2896	5.7

The above typical properties are those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.

#### STORAGE:

All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.

#### HEALTH AND SAFETY:

The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.