



# Prima Pro 20W-40 CH-4

Multigrade Tractor Engine Oil  
Synthetic blend

## PRODUCT DATA SHEET

### Product Description:

Veedol Prima Pro 20W-40 CH-4 diesel engine oil formulated with performance additives to deliver superior performance in tractor engines meeting TREM-III A emission norms.

The synthetic blend with balanced performance additives helps maintain viscosity for longer duration providing extended drain capability. It offers superior protection against wear, corrosion, deposits, and maintains engine cleanliness.

### Performance Specification:

Veedol Prima Pro 20W-40 CH-4 meets and exceeds below performance

API CH-4

### Features/Benefits:

- **Superior soot control:** Special detergent additives prevent soot buildup in the engine, thereby preventing soot-induced thickening and ensuring efficient lubrication.
- **Superior corrosion and wear protection:** High performance additive system provides very good protection to pistons, rings, cylinder liner, and valve train against corrosion and wear.
- **Improved engine cleanliness:** Superior resistance to sludge formation, oil thickening, and deposit control ensure a cleaner engine throughout the recommended oil drain period.

### Application:

- Recommended for all Indian and international tractors meeting TREM-III A and prior emission norms requiring engine oil meeting above specification.
- Suitable for combined harvesters, construction equipment and DG sets as well.
- Recommended oil drain interval 500 hours\*

### Typical Properties:

Parameters	Test Method	Results
Density @ 29.5°C	ASTM D4052	0.853
Kinematic Viscosity @ 40°C, cSt	ASTM D445	103.70
Kinematic Viscosity @ 100°C, cSt	ASTM D445	14.69
Viscosity Index	ASTM D2270	146
Flash Point (COC), °C	ASTM D92	242
Pour Point, °C	ASTM D97	-30
Total Base Number, mg KOH/g	ASTM D2896	7.80

The above typical properties are those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.

#### STORAGE:

All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.

#### HEALTH AND SAFETY:

The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.

\* Oil drain period recommended above is under standard test conditions. It may vary based on actual driving and vehicle condition. Please refer to the vehicle service manual for oil specification and drain interval for specific vehicle types.