



# Take-Off 4T Premium 10W-30 SP / MA2

Premium Four Stroke Motorcycle Engine Oil  
Advanced Synthetic Blend

## PRODUCT DATA SHEET

### Product Description:

Veedol Take-Off 4T Premium 10W-30 SP / MA2 is an advanced synthetic blend engine oil fortified with high performance additives meeting the latest JASO specifications for the modern generation four stroke motorcycles. This high-performance oil helps maintain a cleaner engine and improves efficiency. With its low viscosity, it delivers instant cold starts and enhances fuel efficiency, ensuring optimal performance.

Veedol Take-Off 4T Premium 10W-30 SP / MA2 ensures unmatched protection, excellent thermal stability, and outstanding oxidation resistance, keeping the engine running smoothly under all conditions.

### Performance Specification:

Veedol Take-Off 4T Premium 10W-30 SP / MA2 meets and exceeds below performances

API SP  
JASO MA2 T903: 2023

### Features/Benefits:

- **Reduced friction and improved fuel economy:** The latest friction modifiers minimize internal friction, enhances engine efficiency, and improves fuel economy, ensuring a smoother ride.
- **Unmatched protection:** High performance additives protect highly stressed engine components from sludge, corrosion, deposits, and wear, leading to reduced maintenance costs.
- **Faster clutch engagement and gear response:** The meticulous formulation ensures prompt clutch engagement, enhances gear response, and delivers instant pick-up for a smoother and more responsive riding experience.
- **Advanced synthetic technology:** The advanced synthetic blend offers enhanced performance, and extended oil life for optimal engine operation.

### Application:

- Recommended for modern four stroke motorcycles of leading manufacturers.
- Motorcycles with or without integrated gearbox.
- Suitable for air and water-cooled four stroke engines.
- Compatible with BS VI engines fitted with catalytic converters.

### Typical Properties:

Parameters	Test Method	Results
Density @ 29.5°C	ASTM D4052	0.851
Kinematic Viscosity @ 40°C, cSt	ASTM D445	66.81
Kinematic Viscosity @ 100°C, cSt	ASTM D445	10.69
Viscosity Index	ASTM D2270	149
Flash Point (COC), °C	ASTM D92	238
Pour Point, °C	ASTM D97	-39
Total Base Number, mg KOH/g	ASTM D2896	7.1

The above typical properties are those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.

#### STORAGE:

All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.

#### HEALTH AND SAFETY:

The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.