



PRODUCT DATA SHEET

Product Description:

Veedol Adacut Mist Pro series lubricants are specially formulated to lubricate the parts by oil-mist method. The meticulous formulation ensures effective mist generation and lubricant performance under severe operating conditions.

Features/Benefits:

- **High load carrying capability** resists wear ensuring trouble-free operations, enhances component life and reduces maintenance cost.
- **Effective corrosion protection** ensures long term protection of components.
- **Very good water resistance** provides continued lubrication preventing damage to the components.

Application:

- Lubrication of calendar bearings and sugar mill roller bearings.
- Suitable for steam engines operating under saturated steam conditions.
- Also recommended for lubrication of worm gears.

Typical Properties:

Parameters	Test Method	100	150	355
Kinematic Viscosity @ 40°C, cSt	ASTM D445	98.8	148.7	225.5
Kinematic Viscosity @ 100°C, cSt	ASTM D445	11.16	14.47	19.06
Viscosity Index	ASTM D2270	97	95	95
Flash Point (COC), °C	ASTM D92	234	250	260
Pour Point, °C	ASTM D97	-9	-9	-6

The above typical properties are those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.

STORAGE:

All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.

HEALTH AND SAFETY

The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.