



Product Description:

Veedol Sprint 15W-40 CF-4 engine oil is formulated with advanced mineral technology to meet the rigorous demands of heavy-duty diesel engines.

Veedol Sprint 15W-40 CF-4 provides reliable lubrication, assured wear protection, good deposit control, and enhanced oxidation stability, ensuring the engine operates efficiently. Its advanced mineral formula helps maintain optimal viscosity, extending engine life and reducing maintenance costs.

Performance Specification:

Veedol Sprint 15W-40 meets and exceeds below performance

API CF-4/SF	MB 228.1
ACEA E2-96	Deutz DQC I-02
	MAN 271

Features/Benefits:

- **Assured protection:** Active anti-wear technology provides protection to pistons, rings, cylinder liner lowering servicing cost.
- **Minimized piston deposit:** Special detergent additives prevent soot buildup on piston, minimize ring sticking and engine wear.
- **Enhanced corrosion protection:** Superior corrosion protection formula enhances engine performance and reliability.

Application:

- Heavy-duty diesel vehicles conforming to BS II and prior emission norms.
- Turbo-charged or naturally aspirated diesel engines.
- Recommended oil drain interval 18,000Km*

Typical Properties:

Parameters	Test Method	Results
Density @ 29.5°C	ASTM D4052	0.867
Kinematic Viscosity @ 40°C, cSt	ASTM D445	107.50
Kinematic Viscosity @ 100°C, cSt	ASTM D445	14.40
Viscosity Index	ASTM D2270	137
Flash Point (COC), °C	ASTM D92	230
Pour Point, °C	ASTM D97	-30

The above typical properties are those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.

STORAGE:

All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.

HEALTH AND SAFETY:

The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.

* Oil drain period recommended above is under standard test conditions. It may vary based on actual driving and vehicle condition. Please refer to the vehicle service manual for oil specification and drain interval for specific vehicle types.