



Sprint 15W-40 CI-4 Plus

Heavy-duty Diesel Engine Oil
Advanced mineral

PRODUCT DATA SHEET

Product Description:

Veedol Sprint 15W-40 CI-4 Plus is a heavy-duty diesel engine oil formulated with high-performance additives, ensuring protection and performance in engines meeting BS IV and older emission norms.

The advanced mineral blend provides assured protection against wear, deposits, and soot-related viscosity increase, ensuring optimal engine cleanliness and durability. Designed for use in both on-highway and off-highway applications, it excels in harsh operating environments, delivering good thermal and oxidation stability to provide reliable performance and extend the life of your engines.

Performance Specification:

Veedol Sprint 15W-40 CI-4 Plus meets and exceeds below performance

API CI-4 Plus	Cummins CES 20077 / 76
ACEA E7-08	Volvo VDS-3
	MB 228.3

Features/Benefits:

- **Assured protection:** High performance additive system provides good wear protection to pistons, rings, cylinder liner, and valve train.
- **Optimal engine cleanliness:** Resistance to sludge formation, oil thickening, and deposit control ensure a cleaner engine throughout the recommended oil drain period.
- **Enhanced viscosity control:** Advanced mineral blend provides very good viscosity control, resisting thermal and oxidation degradation of the oil throughout the drain period.

Application:

- On-highway and off-highway heavy-duty diesel vehicles meeting BS IV norms.
- Naturally aspirated and turbocharged diesel engines.
- Mixed fleet of BS IV and older generation vehicles.
- Recommended oil drain interval 60,000Km*

Typical Properties:

Parameters	Test Method	Results
Density @ 29.5°C	ASTM D4052	0.865
Kinematic Viscosity @ 40°C, cSt	ASTM D445	108.28
Kinematic Viscosity @ 100°C, cSt	ASTM D445	14.70
Viscosity Index	ASTM D2270	140
Flash Point (COC), °C	ASTM D92	250
Pour Point, °C	ASTM D97	-30
Total Base Number, mg KOH/g	ASTM D2896	8.8

The above typical properties are those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.

STORAGE:

All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.

HEALTH AND SAFETY:

The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.

* Oil drain period recommended above is under standard test conditions. It may vary based on actual driving and vehicle condition. Please refer to the vehicle service manual for oil specification and drain interval for specific vehicle types.