



Transgear Dex III

Automatic Transmission Fluid

Previous name: Trans D3

PRODUCT DATA SHEET

Product Description:

Veedol Transgear Dex III is a high-quality automatic transmission fluid made from highly refined base stocks and carefully selected additives. It exhibits enhanced frictional property, superior wear protection, oxidation stability, and seal compatibility.

Veedol Transgear Dex III ensures smooth, reliable, and long-lasting transmission performance.

Performance Specification:

Veedol Transgear Dex III meets & exceeds below performance

GM Dex IIIH / IIID / IIE	Allison TES-389	Ford Vehicles (Pre 2005)
GM Type A Suffix A	Allison C-4	

Features/Benefits:

- **Excellent frictional characteristics and wear protection** safeguards transmission components against wear and pitting, reducing maintenance costs.
- **High resistance to oxidation and thermal degradation** reduces deposits and extends the life of transmission components by resisting the effects of oxidizing agents and thermal stress.
- **Excellent compatibility** with transmission seal materials reduces the risk of leakages.

Application:

- Suitable for automatic transmissions, hydraulic systems, torque converters and couplers, and power steering systems where Dexron III fluid is recommended by the manufacturer.

Typical Properties:

Parameters	Test Method	Values
Density at 29.5°C	ASTM D4052	0.855
Kinematic Viscosity @ 40°C, cSt	ASTM D445	36.33
Kinematic Viscosity @ 100°C, cSt	ASTM D445	7.5
Viscosity Index	ASTM D2270	180
Flash Point (COC), °C	ASTM D92	218
Pour Point, °C	ASTM D97	-45

The above typical properties are those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.

STORAGE:

All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.

HEALTH AND SAFETY

The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.